

Flash Disk Module (FDM) Horizontal Mount 40/44 Pin IDE



40-pin Horizontal Mount FDM



44-pin Horizontal Mount FDM

Super Talent's Flash Disk Module (FDMs) provide non-volatile storage in a compact design, making a perfect fit for embedded applications. This FDM model mounts horizontally and is available with either a 40- or 44-pin IDE interface. While typical spinning hard disk drives are the weakest point when it comes to withstanding extremes, FDM's are an asset and ideal to use in severe environments.

Other benefits of FDMs are that they are rugged, lightweight, silent, and have low power consumption. Features include:

- MLC or SLC NAND Flash options
- Platform Independence
- Fast Time to Market - No Driver Required
- Hamming Code-Based EDC/ECC
- 160bit internal and external operation from 4GB - 32GB capacity
- IDE Master/Slave Modes of Operation

Physical Specifications

Mount Type	Horizontal	
*Capacity	4GB - 32GB	
Interface	40- or 44-pin IDE	
Modes	PIO modes 0-4	
OS Support	All	
NAND Flash	MLC / SLC	
Power Supply	5Vcc ± 10%	
Current	Active Mode	55 mA (max)
	Sleep/Idle Mode	0.18 mA (max)

Environmental Specifications

Shock (operating)	10G, 3 axis
Vibration (operating)	1G, each axis
Storage Temperature	-55°C to +80°C

Performance Specifications

Seq. Read	MLC	80 MB/sec
	SLC	80 MB/sec
Seq. Write	MLC	40 MB/sec
	SLC	60 MB/sec
Access Time	0.1 ms	
Track to Track Seek	0.1 ms	
Bus Tx Speed	16.7 MB/sec (peak time)	

Endurance Specifications

MTBF	+1,000,000 hours	
Data Reliability	Built-in EDC/ECC function	
Data Integrity	10 years	
Wear Leveling	Patent Pending	
Write/Erase	MLC	10,000 cycles
	SLC	100,000 cycles
Read	Unlimited	

Flash Disk Module (FDM)

Horizontal Mount 40/44 Pin IDE

Ordering Information: 40-Pin Horizontal

	MLC	SLC
4GB	--	SF4GA4F41
8GB	SF8GB5F41	SF8GA5F41
16GB	SF16B6F41	SF16A6F41
32GB	SF32B7F41	--

Ordering Information: 44-Pin Horizontal

	MLC	SLC
4GB	--	SF4GA4F45
8GB	SF8GB5F45	SF8GA5F45
16GB	SF16B6F45	SF16A6F45
32GB	SF32B7F45	--

Pin Assignment

Pin #	Signal	Function	Pin #	Signal	Function
1	RESET#	Host Reset	2	GND	Ground
3	HD7	Host Data Bit 7	4	HD8	Host Data Bit 8
5	HD6	Host Data Bit 6	6	HD9	Host Data Bit 9
7	HD5	Host Data Bit 5	8	HD10	Host Data Bit 10
9	HD4	Host Data Bit 4	10	HD11	Host Data Bit 11
11	HD3	Host Data Bit 3	12	HD12	Host Data Bit 12
13	HD2	Host Data Bit 1	14	HD13	Host Data Bit 13
15	HD1	Host Data Bit 1	16	HD14	Host Data Bit 14
17	HD0	Host Data Bit 0	18	HD15	Host Data Bit 15
19	GND	Ground	20	NC	Not Connected
21	DMARQ		22	GND	Ground
23	HIOW#	Host I/O Write	24	GND	Ground
25	HIOR#	Host I/O Read	26	GND	Ground
27	IORDY	I/O Ready	28	CSEL	Master/Slave Select
29	DMACK#		30	GND	Ground
31	INTRQ	Interrupt Request	32	IOIS16#	CS I/O 16-bit
33	HA1	Host Address Bit 1	34	PDIAG#	Passed Diagnostics
35	HA0	Host Address Bit 0	36	HA2	Host Address Bit 2
37	CS0#	Chip Select 0	38	CS1#	Chip Select 1
39	DASP#	Drive Active/Drive 1 Pres.	40	GND	Ground
41 ¹⁾	VCC	Supply Voltage	42 ¹⁾	VCC	Supply Voltage
43 ¹⁾	GND	Ground	44 ¹⁾	RESERVED	Reserved

1) Flash Disk Module 40-pin version does not contain pins 41 - 44

NC = These pins are not connected internally

RESERVED = All reserved signals must be left floating