

3.5" SATA Solid State Drive Industrial Temp

General Description

The SATA Flash Drive FSD16/32/64/28/56GC35I series is a Serial ATA interface solid state disk (SSD) drive that features a flash disk controller chip and NAND type flash memory devices. This 3.5 inch form factor SSD series is available in 16GB, 32GB, 64GB, 128GB and 256GB capacities. The drive uses a 5-volt power supply and supports SATA data transfer. This SATA SSD Drive is geared specifically to military and industrial markets for use in such products as avionics, video on demand, ATM, factory automation machines, POS terminals, measuring products, ticket vending machines, parking systems and other industrial products that require an extended temperature range and high tolerance to environmental conditions.

Features

- Capacity: 16GB to 256GB
- Form factor: 3.5 inch type (HDD compatible)
- SATA interface: Serial ATA command set compatible
- Power supply: Vcc=5.0V +/-5%
- Operating temperature: □ Industrial: -40C to +85C
- Performance:
 - Sequential Read Rate: □ 65MB/sec (max)
 - Sequential Write Rate: □ 50MB/sec (max)
 - Sequential Read IOPS: □ 58,675 IOPS
 - Access Time: □ □ 0.1ms
- Shock: 1500G (operating)
- Vibration: 16G (operating)

Specifications

- Compatibility: Full SATA hard disk compatible
- OS Support: All
- Package: Complete metal housing
- Reliability:
 - MTBF: >1,000,000 hours
 - Data reliability: Built-in EDC/ECC function
 - Patent pending Wear-leveling algorithms
- Endurance: □
 - Read: Unlimited
 - Write/Erase: >140 years @ 50GB write-erase /day



Designed and Manufactured in USA

Ordering Information

Capacity	Model No.
16GB	FSD16GC35I
32GB	FSD32GC35I
64GB	FSD64GC35I
128GB	FSD28GC35I
256GB	FSD56GC35I

3.5" SATA Solid State Drive Industrial Temp

SATA Flash Drive Pin Assignment

Signal Segment

Pin	Signal Name	Description
S1	GND	
S2	RxP	Differential Signal Pair for Receive
S3	RxN	
S4	GND	
S5	TxN	Differential Signal Pair for Receive
S6	TxP	
S7	GND	

Power Segment

Pin	Signal Name	Description
P1	Not Used (3.3V)	N/A
P2	Not Used (3.3V)	N/A
P3	Not Used (3.3V Precharge)	
P4	GND	1st mate
P5	GND	2nd mate
P6	GND	
P7	5V Precharge	5V Power
P8	5V Precharge	5V Power
P9	5V Precharge	
P10	GND	
P11	Reserved	
P12	GND	1st mate
P13	Not Used (12V Precharge)	N/A
P14	Not Used (12V)	
P15	Not Used (12V)	

Revision History

Aug 17, 2007 □ Rev-A Preliminary Product Specification Released

Nov 16, 2007 Rev-B Added 256GB

March 21, 2008 Rev-C Revised Photo

